

This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING

1.1 Product identifier: EXG0170900 - MTN MURAL Protective Varnish

Other means of identification:

Non-applicable

1.2 Relevant identified uses of the substance or mixture and uses advised against:

Relevant uses: Varnish

Uses advised against: All uses not specified in this section or in section 7.3

1.3 Details of the supplier of the safety data sheet:

MONTANA COLORS, S.L.

Pol. Ind. Pla de les Vives C/ Anaïs Nin 6

08295 Sant Vicenç de Castellet - Barcelona - España Phone: +34 938332760 (9:00- 16:00h GMT +1:00)

msds@montanacolors.com https://www.montanacolors.com

1.4 Emergency telephone number: +34 938332760 (Mon- frid 9:00- 16:00h GMT +1:00)

SECTION 2: HAZARDS IDENTIFICATION

2.1 Classification of the substance or mixture:

CLP Regulation (EC) No 1272/2008:

Classification of this product has been carried out in accordance with CLP Regulation (EC) No 1272/2008.

Aquatic Chronic 3: Hazardous to the aquatic environment, long-term hazard, Category 3, H412

2.2 Label elements:

CLP Regulation (EC) No 1272/2008:

Hazard statements:

Aquatic Chronic 3: H412 - Harmful to aquatic life with long lasting effects.

Precautionary statements:

P101: If medical advice is needed, have product container or label at hand.

P102: Keep out of reach of children.

P273: Avoid release to the environment.

P501: Dispose of contents/container according to the separated collection system used in your municipality.

Supplementary information:

EUH208: Contains 1,2-benzisothiazol-3(2H)-one, 1,2-benzisothiazol-3(2H)-one, Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate, Hydroxyphenyl benzotriazol derivative, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1). May produce an allergic reaction.

2.3 Other hazards:

Product fails to meet PBT/vPvB criteria

Endocrine-disrupting properties: The product fails to meet the criteria.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS

3.1 Substance:

Non-applicable

3.2 Mixture:

Chemical description: Aqueous mixture composed of additives and resins

Components:

In accordance with Annex II of Regulation (EC) No 1907/2006 (point 3), the product contains:

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 1/14** (Replaced 1)

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS (continued)

	Identification	Chemical name/Classification					
CAS:	121-44-8	triethylamine(1)	riethylamine ⁽¹⁾ Self-classified				
EC: Index: REACH:	204-469-4 612-004-00-5 01-2119475467-26- XXXX	Regulation 1272/2008	Acute Tox. 3: H311+H331; Acute Tox. 4: H302; Eye Dam. 1: H318; Flam. Liq. 2: H225; Skin Corr. 1A: H314; STOT SE 3: H335 - Danger		0,3 - <1 %		
CAS:	34590-94-8	Dipropylene Glycol N	1ethyl Ether ⁽²⁾	Not classified			
EC: Index: REACH:	252-104-2 Non-applicable 01-2119450011-60- XXXX	Regulation 1272/2008			0,3 - <1 %		
CAS:	41556-26-7	Bis(1,2,2,6,6-pentan	nethyl-4-piperidyl) sebacate ⁽¹⁾	Self-classified			
EC: Index: REACH:	255-437-1 Non-applicable Non-applicable	Regulation 1272/2008	Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Skin Sens. 1: H317 - Warning		0,05 - <0,3 %		
CAS: Non-applicable		Hydroxyphenyl benz	roxyphenyl benzotriazol derivative ⁽¹⁾				
EC: Index: REACH:	400-830-7 607-176-00-3 01-0000015075-76- XXXX	Regulation 1272/2008	Aquatic Chronic 2: H411; Skin Sens. 1: H317 - Warning	€	0,05 - <0,3 %		
CAS:	2634-33-5	1,2-benzisothiazol-3	(2H)-one ⁽¹⁾	Self-classified			
EC: Index: REACH:	220-120-9 613-088-00-6 01-2120761540-60- XXXXX Regulation 1272/2008		· (!) (\$\frac{1}{4}\)	<0,05 %			
CAS:	2634-33-5	1,2-benzisothiazol-3	(2H)-one ⁽¹⁾	ATP CLP00			
EC: 220-120-9 Index: 613-088-00-6 REACH: 01-2120761540-60- XXXX		Regulation 1272/2008	Acute Tox. 4: H302; Aquatic Acute 1: H400; Eye Dam. 1: H318; Skin Irrit. 2: H315 Skin Sens. 1: H317 - Danger		<0,05 %		
CAS: EC:	55965-84-9 Non-applicable	reaction mass of 5-c 3-one (3:1) ⁽¹⁾	hloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-	ATP ATP13			
Index: REACH:	613-167-00-5 Non-applicable	Regulation 1272/2008	Acute Tox. 2: H310+H330; Acute Tox. 3: H301; Aquatic Acute 1: H400; Aquatic Chronic 1: H410; Eye Dam. 1: H318; Skin Corr. 1C: H314; Skin Sens. 1A: H317; EUH071 - Danger		<0,05 %		

⁽¹⁾ Substances presenting a health or environmental hazard which meet criteria laid down in Regulation (EU) No. 2020/878 (2) Substance with a Union workplace exposure limit

To obtain more information on the hazards of the substances consult sections 11, 12 and 16.

Other information:

Identification		M-factor
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	Acute	100
CAS: 55965-84-9 EC: Non-applicable	Chronic	100

Identification	Specific concentration limit
triethylamine CAS: 121-44-8 EC: 204-469-4	% (w/w) >=1: STOT SE 3 - H335
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	% (w/w) >=0,05: Skin Sens. 1 - H317
1,2-benzisothiazol-3(2H)-one CAS: 2634-33-5 EC: 220-120-9	% (w/w) >=0,05: Skin Sens. 1 - H317
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) CAS: 55965-84-9 EC: Non-applicable	% (w/w) >=0,6: Skin Corr. 1C - H314 0,06<= % (w/w) <0,6: Skin Irrit. 2 - H315 % (w/w) >=0,6: Eye Dam. 1 - H318 0,06<= % (w/w) <0,6: Eye Irrit. 2 - H319 % (w/w) >=0,0015: Skin Sens. 1A - H317

SECTION 4: FIRST AID MEASURES

4.1 **Description of first aid measures:**

The symptoms resulting from intoxication can appear after exposure, therefore, in case of doubt, seek medical attention for direct exposure to the chemical product or persistent discomfort, showing the SDS of this product.

By inhalation:

- CONTINUED ON NEXT PAGE -

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 Page 2/14 (Replaced 1)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 4: FIRST AID MEASURES (continued)

This product is not classified as hazardous through inhalation. However, in case of intoxication symptoms it is recommended to remove the person affected from the area of exposure, provide clean air and keep at rest. Request medical attention if symptoms persist.

By skin contact:

This product is not classified as hazardous when in contact with the skin. However, in case of skin contact it is recommended to remove contaminated clothes and shoes, rinse the skin or if necessary shower the affected person thoroughly with cold water and neutral soap. In case of serious reaction consult a doctor.

By eye contact:

Rinse eyes thoroughly with water for at least 15 minutes. If the injured person uses contact lenses, these should be removed unless they are stuck to the eyes, in which case removal could cause further damage. In all cases, after cleaning, a doctor should be consulted as quickly as possible with the SDS for the product.

By ingestion/aspiration:

Do not induce vomiting, but if it does happen keep the head down to avoid aspiration. Keep the person affected at rest. Rinse out the mouth and throat, as they may have been affected during ingestion.

4.2 Most important symptoms and effects, both acute and delayed:

Acute and delayed effects are indicated in sections 2 and 11.

4.3 Indication of any immediate medical attention and special treatment needed:

Non-applicable

SECTION 5: FIREFIGHTING MEASURES

5.1 Extinguishing media:

Suitable extinguishing media:

Product is non-flammable under normal conditions of storage, manipulation and use, but the product contains flammable substances. In the case of inflammation as a result of improper manipulation, storage or use preferably use polyvalent powder extinguishers (ABC powder), in accordance with the Regulation on fire protection systems.

Unsuitable extinguishing media:

IT IS RECOMMENDED NOT to use full jet water as an extinguishing agent.

5.2 Special hazards arising from the substance or mixture:

As a result of combustion or thermal decomposition reactive sub-products are created that can become highly toxic and, consequently, can present a serious health risk.

5.3 Advice for firefighters:

Depending on the magnitude of the fire it may be necessary to use full protective clothing and self-contained breathing apparatus (SCBA). Minimum emergency facilities and equipment should be available (fire blankets, portable first aid kit,...) in accordance with Directive 89/654/EC.

Additional provisions:

Act in accordance with the Internal Emergency Plan and the Information Sheets on actions to take after an accident or other emergencies. Eliminate all sources of ignition. In case of fire, cool the storage containers and tanks for products susceptible to combustion, explosion or BLEVE as a result of high temperatures. Avoid spillage of the products used to extinguish the fire into an aqueous medium.

SECTION 6: ACCIDENTAL RELEASE MEASURES

6.1 Personal precautions, protective equipment and emergency procedures:

For non-emergency personnel:

Isolate leaks provided that there is no additional risk for the people performing this task. Evacuate the area and keep out those without protection. Personal protection equipment must be used against potential contact with the spilt product (See section 8). Above all prevent the formation of any vapour-air flammable mixtures, through either ventilation or the use of an inert medium. Remove any source of ignition. Eliminate electrostatic charges by interconnecting all the conductive surfaces on which static electricity could form, and also ensuring that all surfaces are connected to the ground.

- CONTINUED ON NEXT PAGE -

Page 3/14

For emergency responders:

See section 8.

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2

(Replaced 1)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 6: ACCIDENTAL RELEASE MEASURES (continued)

6.2 Environmental precautions:

Avoid at all cost any type of spillage into an aqueous medium. Contain the product absorbed appropriately in hermetically sealed containers. Notify the relevant authority in case of exposure to the general public or the environment.

6.3 Methods and material for containment and cleaning up:

It is recommended:

Absorb the spillage using sand or inert absorbent and move it to a safe place. Do not absorb in sawdust or other combustible absorbents. For any concern related to disposal consult section 13.

6.4 Reference to other sections:

See sections 8 and 13.

SECTION 7: HANDLING AND STORAGE

7.1 Precautions for safe handling:

A.- General precautions for safe use

Comply with the current legislation concerning the prevention of industrial risks with regards manually handling weights. Maintain order, cleanliness and destroy using safe methods (section 6).

B.- Technical recommendations for the prevention of fires and explosions

Avoid the evaporation of the product as it contains flammable substances, which could form flammable vapour/air mixtures in the presence of sources of ignition. Control sources of ignition (mobile phones, sparks,...) and transfer at slow speeds to avoid the creation of electrostatic charges. Consult section 10 for conditions and materials that should be avoided.

C.- Technical recommendations on general occupational hygiene

Do not eat or drink during the process, washing hands afterwards with suitable cleaning products.

D.- Technical recommendations to prevent environmental risks

Due to the danger of this product for the environment it is recommended to use it within an area containing contamination control barriers in case of spillage, as well as having absorbent material in close proximity.

7.2 Conditions for safe storage, including any incompatibilities:

A.- Technical measures for storage

Minimum Temp.: 5 °C

Maximum Temp.: 30 °C

Maximum time: 60 Months

B.- General conditions for storage

Avoid sources of heat, radiation, static electricity and contact with food. For additional information see subsection 10.5

7.3 Specific end use(s):

Except for the instructions already specified it is not necessary to provide any special recommendation regarding the uses of this product.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION

8.1 Control parameters:

Substances whose occupational exposure limits have to be monitored in the workplace (European OEL, not country-specific legislation):


Directive (EU) 2000/39, Directive 2004/37/EC, Directive (EU) 2006/15, Directive (EU) 2009/161, Directive (EU) 2017/164, Directive (EU) 2019/1831:

Identification	Occup	Occupational exposure limits		
triethylamine	IOELV (8h)	2 ppm	8,4 mg/m ³	
CAS: 121-44-8 EC: 204-469-4	IOELV (STEL)	3 ppm	12,6 mg/m ³	
Dipropylene Glycol Methyl Ether	IOELV (8h)	50 ppm	308 mg/m ³	
CAS: 34590-94-8	IOELV (STEL)			

DNEL (Workers):

- CONTINUED ON NEXT PAGE
Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 Page 4/14

Printing: 20/07/2022 (Replaced 1)





This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

		Short exposure		Long exposure	
Identification		Systemic	Local	Systemic	Local
triethylamine	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 121-44-8	Dermal	Non-applicable	Non-applicable	12,1 mg/kg	Non-applicable
EC: 204-469-4	Inhalation	12,6 mg/m ³	12,6 mg/m ³	8,4 mg/m ³	8,4 mg/m ³
Dipropylene Glycol Methyl Ether	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 34590-94-8	Dermal	Non-applicable	Non-applicable	283 mg/kg	Non-applicable
EC: 252-104-2	Inhalation	Non-applicable	Non-applicable	308 mg/m ³	Non-applicable
Hydroxyphenyl benzotriazol derivative	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	0,5 mg/kg	Non-applicable
EC: 400-830-7	Inhalation	Non-applicable	Non-applicable	0,35 mg/m ³	Non-applicable
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,966 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	6,81 mg/m ³	Non-applicable
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,966 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	6,81 mg/m ³	Non-applicable

DNEL (General population):

		Short	Short exposure		exposure
Identification		Systemic	Local	Systemic	Local
Dipropylene Glycol Methyl Ether	Oral	Non-applicable	Non-applicable	36 mg/kg	Non-applicable
CAS: 34590-94-8	Dermal	Non-applicable	Non-applicable	121 mg/kg	Non-applicable
EC: 252-104-2	Inhalation	Non-applicable	Non-applicable	37,2 mg/m ³	Non-applicable
Hydroxyphenyl benzotriazol derivative	Oral	Non-applicable	Non-applicable	0,025 mg/kg	Non-applicable
CAS: Non-applicable	Dermal	Non-applicable	Non-applicable	0,25 mg/kg	Non-applicable
EC: 400-830-7	Inhalation	Non-applicable	Non-applicable	0,085 mg/m ³	Non-applicable
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,345 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	1,2 mg/m ³	Non-applicable
1,2-benzisothiazol-3(2H)-one	Oral	Non-applicable	Non-applicable	Non-applicable	Non-applicable
CAS: 2634-33-5	Dermal	Non-applicable	Non-applicable	0,345 mg/kg	Non-applicable
EC: 220-120-9	Inhalation	Non-applicable	Non-applicable	1,2 mg/m ³	Non-applicable

PNEC:

Identification				
triethylamine	STP	100 mg/L	Fresh water	0,11 mg/L
CAS: 121-44-8	Soil	0,25 mg/kg	Marine water	0,011 mg/L
EC: 204-469-4	Intermittent	0,08 mg/L	Sediment (Fresh water)	1,575 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,158 mg/kg
Dipropylene Glycol Methyl Ether	STP	4168 mg/L	Fresh water	19 mg/L
CAS: 34590-94-8	Soil	2,74 mg/kg	Marine water	1,9 mg/L
EC: 252-104-2	Intermittent	190 mg/L	Sediment (Fresh water)	70,2 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	7,02 mg/kg
Hydroxyphenyl benzotriazol derivative	STP	10 mg/L	Fresh water	0,002 mg/L
CAS: Non-applicable	Soil	2 mg/kg	Marine water	0 mg/L
EC: 400-830-7	Intermittent	0,028 mg/L	Sediment (Fresh water)	3,37 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,337 mg/kg
1,2-benzisothiazol-3(2H)-one	STP	1,03 mg/L	Fresh water	0,00403 mg/L
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0,000403 mg/L
EC: 220-120-9	Intermittent	0,0011 mg/L	Sediment (Fresh water)	0,0499 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00499 mg/kg

- CONTINUED ON NEXT PAGE -

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 5/14** (Replaced 1)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

Identification				
1,2-benzisothiazol-3(2H)-one	STP	1,03 mg/L	Fresh water	0,00403 mg/L
CAS: 2634-33-5	Soil	3 mg/kg	Marine water	0,000403 mg/L
EC: 220-120-9	Intermittent	0,0011 mg/L	Sediment (Fresh water)	0,0499 mg/kg
	Oral	Non-applicable	Sediment (Marine water)	0,00499 mg/kg

8.2 Exposure controls:

A.- Individual protection measures, such as personal protective equipment

As a preventative measure it is recommended to use basic Personal Protective Equipment, with the corresponding <<CE marking>> in accordance with Regulation (EU) 2016/425. For more information on Personal Protective Equipment (storage, use, cleaning, maintenance, class of protection,...) consult the information leaflet provided by the manufacturer. For more information see subsection 7.1. All information contained herein is a recommendation which needs some specification from the labour risk prevention services as it is not known whether the company has additional measures at its disposal.

B.- Respiratory protection

The use of protection equipment will be necessary if a mist forms or if the occupational exposure limits are exceeded.

C.- Specific protection for the hands

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory hand protection	Chemical protective gloves (Material: Linear low-density polyethylene (LLDPE), Breakthrough time: > 480 min, Thickness: 0.062 mm)	CAT III	EN 420:2004+A1:2010	Replace the gloves at any sign of deterioration.

As the product is a mixture of several substances, the resistance of the glove material can not be calculated in advance with total reliability and has therefore to be checked prior to the application.

D.- Eye and face protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
Mandatory face protection	Panoramic glasses against splash/projections.	CATII	EN 166:2002 EN ISO 4007:2018	Clean daily and disinfect periodically according to the manufacturer's instructions. Use if there is a risk of splashing.

E.- Body protection

Pictogram	PPE	Labelling	CEN Standard	Remarks
	Work clothing	CATI		Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 6529:2013, EN ISO 6530:2005, EN ISO 13688:2013, EN 464:1994.
	Anti-slip work shoes	CAT II	EN ISO 20347:2012	Replace before any evidence of deterioration. For periods of prolonged exposure to the product for professional/industrial users CE III is recommended, in accordance with the regulations in EN ISO 20345:2012 y EN 13832-1:2007

F.- Additional emergency measures

Emergency measure	Standards	Emergency measure	Standards
-3	ANSI Z358-1 ISO 3864-1:2011, ISO 3864-4:2011	⊢	DIN 12 899 ISO 3864-1:2011, ISO 3864-4:2011
Emergency shower		Eyewash stations	

Environmental exposure controls:

In accordance with the community legislation for the protection of the environment it is recommended to avoid environmental spillage of both the product and its container. For additional information see subsection 7.1.D

Volatile organic compounds:

With regard to Directive 2010/75/EU, this product has the following characteristics:

V.O.C. (Supply): 1,36 % weight

- CONTINUED ON NEXT PAGE -

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 6/14** (Replaced 1)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION (continued)

V.O.C. density at 20 °C: 14,33 kg/m³ (14,33 g/L)

Average carbon number: 6,4

Average molecular weight: 121,25 g/mol

With regard to Directive 2004/42/EC, this product which is ready to use has the following characteristics:

V.O.C. density at 20 °C: 98,67 kg/m³ (98,67 g/L)

EU limit for the product (Cat. A.E): 130 g/L (2010) Components: Non-applicable

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES

9.1 Information on basic physical and chemical properties:

For complete information see the product datasheet.

Appearance:

Physical state at 20 °C:

Appearance:

Not available

Colour:

Odour:

Not available

Not available

Nour threshold:

Non-applicable *

Volatility:

Boiling point at atmospheric pressure: 106 °C Vapour pressure at 20 °C: 2292 Pa

Vapour pressure at 50 °C: 12049,5 Pa (12,05 kPa)

Evaporation rate at 20 °C: Non-applicable *

Product description:

Density at 20 °C: 1053,2 kg/m³

Relative density at 20 °C: 1,053

Dynamic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Kinematic viscosity at 20 °C:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

PH:

9,5 - 10,5

Vapour density at 20 °C:

Non-applicable *

Partition coefficient n-octanol/water 20 °C:

Non-applicable *

Solubility in water at 20 °C:

Non-applicable *

Non-applicable *

Non-applicable *

Non-applicable *

Mon-applicable *

Non-applicable *

Mon-applicable *

Non-applicable *

Flammability:

Flash Point: Non Flammable (>60 °C)

Flammability (solid, gas): Non-applicable *

Autoignition temperature: 189 °C

Lower flammability limit: Non-applicable *
Upper flammability limit: Non-applicable *

Particle characteristics:

*Not relevant due to the nature of the product, not providing information property of its hazards.

- CONTINUED ON NEXT PAGE -

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 7/14** (Replaced 1)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES (continued)

Median equivalent diameter: Non-applicable

9.2 Other information:

Information with regard to physical hazard classes:

Explosive properties:

Oxidising properties:

Corrosive to metals:

Heat of combustion:

Aerosols-total percentage (by mass) of flammable

Non-applicable *

Non-applicable *

Non-applicable *

components:

Other safety characteristics:

Surface tension at 20 °C:

Refraction index:

Non-applicable *

Non-applicable *

*Not relevant due to the nature of the product, not providing information property of its hazards.

SECTION 10: STABILITY AND REACTIVITY

10.1 Reactivity:

No hazardous reactions are expected because the product is stable under recommended storage conditions. See section 7.

10.2 Chemical stability:

Chemically stable under the indicated conditions of storage, handling and use.

10.3 Possibility of hazardous reactions:

Under the specified conditions, hazardous reactions that lead to excessive temperatures or pressure are not expected.

10.4 Conditions to avoid:

Applicable for handling and storage at room temperature:

Shock and friction	Contact with air	Increase in temperature	Sunlight	Humidity
Not applicable	Not applicable	Precaution	Precaution	Not applicable

10.5 Incompatible materials:

Acids	Water	Oxidising materials	Combustible materials	Others	
Avoid strong acids	Not applicable	Avoid direct impact	Not applicable	Avoid alkalis or strong bases	

10.6 Hazardous decomposition products:

See subsection 10.3, 10.4 and 10.5 to find out the specific decomposition products. Depending on the decomposition conditions, complex mixtures of chemical substances can be released: carbon dioxide (CO₂), carbon monoxide and other organic compounds.

SECTION 11: TOXICOLOGICAL INFORMATION

11.1 Information on hazard classes as defined in Regulation (EC) No 1272/2008:

The experimental information related to the toxicological properties of the product itself is not available

Contains glycols. It is recommended not to breathe the vapours for prolonged periods of time due to the possibility of effects that are hazardous to the health .

Dangerous health implications:

In case of exposure that is repetitive, prolonged or at concentrations higher than the recommended occupational exposure limits, adverse effects on health may result, depending on the means of exposure:

- A- Ingestion (acute effect):
 - Acute toxicity: Based on available data, the classification criteria are not met, however, it contains substances classified as dangerous for consumption. For more information see section 3.
 - Corrosivity/Irritability: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.

B- Inhalation (acute effect):

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 8/14** (Replaced 1)

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

- Acute toxicity: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.
- Corrosivity/Irritability: Prolonged inhalation of the product is corrosive to mucous membranes and the upper respiratory tract
- C- Contact with the skin and the eyes (acute effect):
 - Contact with the skin: Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for skin contact. For more information see section 3.
 - Contact with the eyes: Based on available data, the classification criteria are not met. However, it does contain substances classified as hazardous for this effect. For more information see section 3.
- D- CMR effects (carcinogenicity, mutagenicity and toxicity to reproduction):
 - Carcinogenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for the effects mentioned. For more information see section 3.

IARC: Non-applicable

- Mutagenicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- Reproductive toxicity: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- E- Sensitizing effects:
 - Respiratory: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous with sensitising effects. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met. However, it contains substances classified as dangerous with sensitising effects. For more information see section 3.
- F- Specific target organ toxicity (STOT) single exposure:

Based on available data, the classification criteria are not met. However, it contains substances classified as hazardous for inhalation. For more information see section 3.

- G- Specific target organ toxicity (STOT)-repeated exposure:
 - Specific target organ toxicity (STOT)-repeated exposure: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
 - Skin: Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.
- H- Aspiration hazard:

Based on available data, the classification criteria are not met, as it does not contain substances classified as hazardous for this effect. For more information see section 3.

Other information:

Non-applicable

Specific toxicology information on the substances:

Identification	Acu	te toxicity	Genus
triethylamine	LD50 oral	730 mg/kg	Rat
CAS: 121-44-8	LD50 dermal	580 mg/kg	Rabbit
EC: 204-469-4	LC50 inhalation	3 mg/L (ATEi)	
Dipropylene Glycol Methyl Ether	LD50 oral	>5000 mg/kg	Rat
CAS: 34590-94-8	LD50 dermal	9510 mg/kg	Rabbit
EC: 252-104-2	LC50 inhalation	>20 mg/L	
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LD50 oral	2615 mg/kg	Rat
CAS: 41556-26-7	LD50 dermal	>2000 mg/kg	
EC: 255-437-1	LC50 inhalation	>20 mg/L	
Hydroxyphenyl benzotriazol derivative	LD50 oral	>2000 mg/kg	
CAS: Non-applicable	LD50 dermal	>2000 mg/kg	
EC: 400-830-7	LC50 inhalation	>20 mg/L	
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	>2000 mg/kg	
EC: 220-120-9	LC50 inhalation	>5 mg/L	

- CONTINUED ON NEXT PAGE -

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 9/14** (Replaced 1)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 11: TOXICOLOGICAL INFORMATION (continued)

Identification	Acu	Genus	
1,2-benzisothiazol-3(2H)-one	LD50 oral	500 mg/kg	Rat
CAS: 2634-33-5	LD50 dermal	>2000 mg/kg	
EC: 220-120-9	LC50 inhalation	>5 mg/L	
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LD50 oral	64 mg/kg	Rat
CAS: 55965-84-9	LD50 dermal	87,12 mg/kg	Rabbit
EC: Non-applicable	LC50 inhalation	0,33 mg/L (4 h)	Rat

11.2 Information on other hazards:

Endocrine disrupting properties

Endocrine-disrupting properties: The product fails to meet the criteria.

Other information

Non-applicable

SECTION 12: ECOLOGICAL INFORMATION

The experimental information related to the eco-toxicological properties of the product itself is not available

12.1 Toxicity:

Acute toxicity:

Identification		Concentration	Species	Genus
triethylamine	LC50	43,7 mg/L (96 h)	Pimephales promelas	Fish
CAS: 121-44-8	EC50	200 mg/L (48 h)	Daphnia magna	Crustacean
EC: 204-469-4	EC50	Non-applicable		
Dipropylene Glycol Methyl Ether	LC50	10000 mg/L (96 h)	Pimephales promelas	Fish
CAS: 34590-94-8	EC50	1919 mg/L (48 h)	Daphnia magna	Crustacean
EC: 252-104-2	EC50	Non-applicable		
Bis(1,2,2,6,6-pentamethyl-4-piperidyl) sebacate	LC50	0,97 mg/L (96 h)	Lepomis macrochirus	Fish
CAS: 41556-26-7	EC50	20 mg/L (24 h)	Daphnia magna	Crustacean
EC: 255-437-1	EC50	Non-applicable		
Hydroxyphenyl benzotriazol derivative	LC50	>1 - 10 (96 h)		Fish
CAS: Non-applicable	EC50	>1 - 10 (48 h)		Crustacean
EC: 400-830-7	EC50	>1 - 10 (72 h)		Algae

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 10/14** (Replaced 1)





This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Concentration		Species	Genus
1,2-benzisothiazol-3(2H)-one	LC50	2,2 mg/L (96 h)	Oncorhynchus mykiss	Fish
CAS: 2634-33-5	EC50	3 mg/L (48 h)	Daphnia magna	Crustacean
EC: 220-120-9	EC50	0,067 mg/L (72 h)	Pseudokirchneriella subcapitata	Algae
1,2-benzisothiazol-3(2H)-one	LC50	>0.1 - 1 (96 h)		Fish
CAS: 2634-33-5	EC50	>0.1 - 1 (48 h)		Crustacean
EC: 220-120-9	EC50	>0.1 - 1 (72 h)		Algae
reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1)	LC50	>0.1 - 1 (96 h)		Fish
CAS: 55965-84-9	EC50	>0.1 - 1 (48 h)		Crustacean
EC: Non-applicable	EC50	>0.1 - 1 (72 h)		Algae

Chronic toxicity:

Identification	Concentration		Species	Genus
triethylamine	NOEC	Non-applicable		
CAS: 121-44-8 EC: 204-469-4	NOEC	11 mg/L	Daphnia magna	Crustacean
Dipropylene Glycol Methyl Ether	NOEC	Non-applicable		
CAS: 34590-94-8 EC: 252-104-2	NOEC	0,5 mg/L	Daphnia magna	Crustacean

12.2 Persistence and degradability:

Identification	Degr	adability	Biodegradal	oility
triethylamine	BOD5	Non-applicable	Concentration	26 mg/L
CAS: 121-44-8	COD	Non-applicable	Period	28 days
EC: 204-469-4	BOD5/COD	Non-applicable	% Biodegradable	85 %
Dipropylene Glycol Methyl Ether	BOD5	Non-applicable	Concentration	Non-applicable
CAS: 34590-94-8	COD	0 g O2/g	Period	28 days
EC: 252-104-2	BOD5/COD	Non-applicable	% Biodegradable	73 %
1,2-benzisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 2634-33-5	COD	Non-applicable	Period	28 days
EC: 220-120-9	BOD5/COD	Non-applicable	% Biodegradable	0 %
1,2-benzisothiazol-3(2H)-one	BOD5	Non-applicable	Concentration	100 mg/L
CAS: 2634-33-5	COD	Non-applicable	Period	28 days
EC: 220-120-9	BOD5/COD	Non-applicable	% Biodegradable	0 %

12.3 Bioaccumulative potential:

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 11/14** (Replaced 1)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 12: ECOLOGICAL INFORMATION (continued)

Identification	Bioaccumulation potential		
triethylamine	BCF	5	
CAS: 121-44-8	Pow Log	1.45	
EC: 204-469-4	Potential	Low	
Dipropylene Glycol Methyl Ether	BCF	1	
CAS: 34590-94-8	Pow Log	-0.06	
EC: 252-104-2	Potential	Low	
1,2-benzisothiazol-3(2H)-one	BCF	2	
CAS: 2634-33-5	Pow Log	1.45	
EC: 220-120-9	Potential	Low	
1,2-benzisothiazol-3(2H)-one	BCF	2	
CAS: 2634-33-5	Pow Log	1.45	
EC: 220-120-9	Potential	Low	

12.4 Mobility in soil:

Identification	Absorption/desorption		Volatility	
triethylamine	Koc	145	Henry	Non-applicable
CAS: 121-44-8	Conclusion	Very High	Dry soil	Non-applicable
EC: 204-469-4	Surface tension	2,024E-2 N/m (25 °C)	Moist soil	Non-applicable

12.5 Results of PBT and vPvB assessment:

Product fails to meet PBT/vPvB criteria

12.6 Endocrine disrupting properties:

Endocrine-disrupting properties: The product fails to meet the criteria.

12.7 Other adverse effects:

Not described

SECTION 13: DISPOSAL CONSIDERATIONS

13.1 Waste treatment methods:

Code	Description	Waste class (Regulation (EU) No 1357/2014)
08 01 11*	waste paint and varnish containing organic solvents or other hazardous substances	Dangerous

Type of waste (Regulation (EU) No 1357/2014):

HP14 Ecotoxic

Waste management (disposal and evaluation):

Consult the authorized waste service manager on the assessment and disposal operations in accordance with Annex 1 and Annex 2 (Directive 2008/98/EC). As under 15 01 (2014/955/EC) of the code and in case the container has been in direct contact with the product, it will be processed the same way as the actual product. Otherwise, it will be processed as non-dangerous residue. Waste should not be disposed of to drains. See paragraph 6.2.

Regulations related to waste management:

In accordance with Annex II of Regulation (EC) No 1907/2006 (REACH) the community or state provisions related to waste management are stated

Community legislation: Directive 2008/98/EC, 2014/955/EU, Regulation (EU) No 1357/2014

SECTION 14: TRANSPORT INFORMATION

This product is not regulated for transport (ADR/RID,IMDG,IATA)

SECTION 15: REGULATORY INFORMATION

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture:

- CONTINUED ON NEXT PAGE -

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 12/14** (Replaced 1)



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 15: REGULATORY INFORMATION (continued)

Regulation (EC) No 528/2012: contains a preservative to protect the initial properties of the treated article. Contains 2-n-butyl-benzo[d]isothiazol-3-one, 1,2-benzisothiazol-3(2H)-one, reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1), 1,2-benzisothiazol-3(2H)-one.

Candidate substances for authorisation under the Regulation (EC) No 1907/2006 (REACH): Non-applicable

Substances included in Annex XIV of REACH ("Authorisation List") and sunset date: Non-applicable

Regulation (EC) No 1005/2009, about substances that deplete the ozone layer: Non-applicable

Article 95, REGULATION (EU) No 528/2012: 1,2-benzisothiazol-3(2H)-one (Product-type 2, 6, 9, 11, 12, 13); 1,2-benzisothiazol-3 (2H)-one (Product-type 2, 6, 9, 11, 12, 13); reaction mass of 5-chloro-2-methyl-2H-isothiazol-3-one and 2-methyl-2H-isothiazol-3-one (3:1) (Product-type 2, 4, 6, 11, 12, 13)

REGULATION (EU) No 649/2012, in relation to the import and export of hazardous chemical products: Non-applicable

Seveso III:

Non-applicable

Limitations to commercialisation and the use of certain dangerous substances and mixtures (Annex XVII REACH, etc):

Shall not be used in:

- —ornamental articles intended to produce light or colour effects by means of different phases, for example in ornamental lamps and ashtrays,
- -tricks and jokes,
- —games for one or more participants, or any article intended to be used as such, even with ornamental aspects.

Contains Decamethylcyclopentasiloxane, Octamethylcyclotetrasiloxane. 1. | Shall not be placed on the market in wash-off cosmetic products in a concentration equal to or greater than 0,1 % by weight of either substance, after 31 January 2020. | 2. | For the purposes of this entry, "wash-off cosmetic products" means cosmetic products as defined in Article 2(1)(a) of Regulation (EC) No 1223/2009 that, under normal conditions of use, are washed off with water after application.'

Occupational exposure to respirable crystalline silica must be controlled pursuant to Directive (EU) 2019/130.

Specific provisions in terms of protecting people or the environment:

It is recommended to use the information included in this safety data sheet as a basis for conducting workplace-specific risk assessments in order to establish the necessary risk prevention measures for the handling, use, storage and disposal of this product.

Other legislation:

The product could be affected by sectorial legislation

15.2 Chemical safety assessment:

The supplier has not carried out evaluation of chemical safety.

SECTION 16: OTHER INFORMATION

Legislation related to safety data sheets:

The SDS shall be supplied in an official language of the country where the product is placed on the market. This safety data sheet has been designed in accordance with ANNEX II-Guide to the compilation of safety data sheets of Regulation (EC) No 1907/2006 (COMMISSION REGULATION (EU) 2020/878).

Modifications related to the previous Safety Data Sheet which concerns the ways of managing risks.:

COMMISSION REGULATION (EU) 2020/878

Texts of the legislative phrases mentioned in section 2:

H412: Harmful to aquatic life with long lasting effects.

Texts of the legislative phrases mentioned in section 3:

The phrases indicated do not refer to the product itself; they are present merely for informative purposes and refer to the individual components which appear in section 3

CLP Regulation (EC) No 1272/2008:

(Replaced 1)

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 13/14**

- CONTINUED ON NEXT PAGE -



This SDS is an English translation of COMMISSION REGULATION (EU) 2020/878, without any country-specific legislation

EXG0170900 - MTN MURAL Protective Varnish

SECTION 16: OTHER INFORMATION (continued)

Acute Tox. 2: H310+H330 - Fatal in contact with skin or if inhaled.

Acute Tox. 3: H301 - Toxic if swallowed.

Acute Tox. 3: H311+H331 - Toxic in contact with skin or if inhaled.

Acute Tox. 4: H302 - Harmful if swallowed. Aquatic Acute 1: H400 - Very toxic to aquatic life.

Aquatic Chronic 1: H410 - Very toxic to aquatic life with long lasting effects. Aquatic Chronic 2: H411 - Toxic to aquatic life with long lasting effects.

Eye Dam. 1: H318 - Causes serious eye damage.

Flam. Liq. 2: H225 - Highly flammable liquid and vapour.

Skin Corr. 1A: H314 - Causes severe skin burns and eye damage. Skin Corr. 1C: H314 - Causes severe skin burns and eye damage.

Skin Irrit. 2: H315 - Causes skin irritation.

Skin Sens. 1: H317 - May cause an allergic skin reaction. Skin Sens. 1A: H317 - May cause an allergic skin reaction. STOT SE 3: H335 - May cause respiratory irritation.

Classification procedure:

Aguatic Chronic 3: Calculation method

Advice related to training:

Training is recommended in order to prevent industrial risks for staff using this product and to facilitate their comprehension and interpretation of this safety data sheet, as well as the label on the product.

Principal bibliographical sources:

http://echa.europa.eu http://eur-lex.europa.eu

Abbreviations and acronyms:

ADR: European agreement concerning the international carriage of dangerous goods by road

IMDG: International maritime dangerous goods code

IATA: International Air Transport Association ICAO: International Civil Aviation Organisation

COD: Chemical Oxygen Demand

BOD5: 5day biochemical oxygen demand

BCF: Bioconcentration factor LD50: Lethal Dose 50

LC50: Lethal Concentration 50 EC50: Effective concentration 50

LogPOW: Octanolwater partition coefficient Koc: Partition coefficient of organic carbon

UFI: unique formula identifier

(Replaced 1)

IARC: International Agency for Research on Cancer

The information contained in this safety data sheet is based on sources, technical knowledge and current legislation at European and state level, without being able to guarantee its accuracy. This information cannot be considered a guarantee of the properties of the product, it is simply a description of the security requirements. The occupational methodology and conditions for users of this product are not within our awareness or control, and it is ultimately the responsibility of the user to take the necessary measures to obtain the legal requirements concerning the manipulation, storage, use and disposal of chemical products. The information on this safety data sheet only refers to this product, which should not be used for needs other than those specified.

Printing: 20/07/2022 Date of compilation: 27/01/2022 Revised: 20/07/2022 Version: 2 **Page 14/14**