



# Product information | TECHNICAL DATA SHEET **GLASS TO MIRROR CONVERTER.**

400 ml, 10.95 Oz, 285 g.

# **GENERAL DESCRIPTION**

Decorative paint with a bright chrome effect, applied to the back of glass.

The MTN PRO Glass to Mirror Converter is a decorative paint especially suitable for turning any glass into a mirror. The product should be applied on the opposite side of the surface to be converted.

## **CHARACTERISTICS**

- Fast-drying.
- High gloss.
- High coverage.
- Does not contain lead.
- Low resistance to weathering.
- Low resistance to rubbing.

### INSTRUCTIONS FOR USE

- Shake the spray can well before use for about one minute after hearing the sound of the mixer ball.
- Apply on clean, dry and completely smooth surfaces.
- Apply in very thin coats for best results. Shake the can during application. Apply until the desired effect is achieved.
- Apply 3-4 layers and, once dry, add a layer of black or dark paint that will enhance the result and protect from scratches, as this product has limited resistance to friction.
- Invert the spray can to purge the valve after use. If the cap becomes clogged replace it with a new one.
- Do not apply to plugged-in electronic equipment and use in well-ventilated areas.

## **GENERAL DESCRIPTION**

Binder type:	Special resin
Color:	Chrome
Dry to the touch (ASTM D-1640 ISO 1517):	10-20'
Total dry time (ASTM D-1640 ISO 1517)	2 h
Thickness of dry coat (ASTM D-823 ISO 2808):	<5 μ/coat
Adherence (ASMT D-3359 ISO 2409)	Not applicable
Theoretical performance:	1,25 m2
Second coat:	after 10-15 min
Solvent:	Acetones
Shelf life:	< 5 yeats (Well Storet)
Application conditions:	Atmospheric temp 15-25°C
	Surface temp. from 10°-30 C
	Maximum humidity 85% R.H.P

<sup>\*</sup> Times may vary depending on thickness of coat.

### **APPLICATION**

This decorative paint for Fine Arts is very suitable for painting glass.

- DIY.
- Fine Arts.
- Plastics.
- Touch-ups on metallic parts.

This product has little resistance to friction/rubbing, thus resulting in a loss of gloss and the mirror effect.

To improve the effect, apply a thin coat of black paint underneath the mirror effect paint. The finish must be totally smooth in order to obtain a good result.

### **APPARENCE**



Protects the valve and cap.

# **PACKAGING**

CAP SYSTEM

Pocket Cap

Nominal capacity 400 ml. Heat resistance of packaging: <50°C Propellant: DME

Box (6 units) 205 X 140 X 200 mm



**CAUTION** 





65 mm









LABEL













